



NOTE: Images are for illustration purposes only. Actual models may differ slightly.

TABLE OF CONTENTS

	PAGE
MODEL NUMBER NOMENCLATURE	3
STANDARD FEATURES AND ACCESSORIES	4
DIMENSIONS	5
CLEARANCES	8
SPECIFICATIONS	9
COOLING PERFORMANCE DATA	11
HEATING PERFORMANCE DATA	13
APPLICATION DATA	15
WIRING	15
AIR FLOW DATA	16
ELECTRICAL DATA	17
WIRING DIAGRAMS	18
GUIDE SPECIFICATIONS	22

INDUSTRY LEADING FEATURES / BENEFITS

A PERFECT BALANCE BETWEEN BUDGET LIMITS, ENERGY, SAVINGS AND COMFORT.

The ductless systems are a matched combination of an outdoor condensing unit and an indoor fan coil unit connected only by refrigerant tubing and wires.

The ductless system permits creative solutions to design problems such as:

- Add-ons to current space (an office or family room addition)
- Special space requirements
- When changes in the load cannot be handled by the existing system
- When adding air conditioning to spaces that are heated by hydronic or electric heat and have no ductwork
- Historical renovations or any application where preserving the look of the original structure is essential

The ideal compliment to your ducted system when it is impractical or prohibitively expensive to use ductwork.

The compact indoor fan coil units take up very little space in the room and do not obstruct windows. The fan coils are attractively styled to blend with most room decors. Advanced system components incorporate innovative technology to provide reliable cooling performance at low sound levels.

INVERTER TECHNOLOGY

The inverter driven compressor is designed to run at various input power frequencies (Hz) which controls the compressor's motor speed.

Even Temperature – The control package, including the inverter, monitors the outdoor and indoor temperatures as they relate to the selected indoor set point and adjusts the compressor speed to match the load and keep the system operating continuously rather than cycling and creating temperature swings. This translates to higher comfort levels for the occupants.

Rapid Pull Down/Warm-Up – Comfort is increased by the inverter system's ability to ramp up the compressor speed enabling the system to reach the user selected room temperature set point quicker.

Humidity Control – Running the system for longer periods and continuously varying the compressor speed enhances the humidity control.

INDIVIDUAL ROOM COMFORT

Maximum comfort is provided because each space can be controlled individually based on the usage pattern.

LOW SOUND LEVELS

When noise is a concern, ductless systems are the answer. The indoor units are whisper quiet. There are no compressors indoors, either in the conditioned space or directly over it, and there is none of the noise usually generated by air being forced through the ductwork.

When sound ordinances and proximity to neighbors demand quiet operation, this outdoor unit is the right choice. With the inverter technology, these units run at lower speeds most of the time resulting in reduced sound levels.

INVERTER TECHNOLOGY – ENHANCED ECONOMICAL OPERATION

Ductless systems are inherently economical to operate. Individual rooms are heated or cooled only when required, and since the air is delivered directly to the space, there is no need to use additional energy to move the air in the ductwork. This economical operation is enhanced further when the inverter system output matches the load resulting in a more efficient system.

EASY-TO-USE CONTROLS

The systems have microprocessor-based controls to provide the ultimate in comfort and efficiency. The user friendly wired and wireless remote controls provide the interface between the user and the unit.

SECURE OPERATION

If security is an issue, outdoor and indoor units are connected only by refrigerant piping and wiring to prevent intruders from crawling through ductwork or wall openings. In addition, since the outdoor unit can be installed close to an outside wall, coils are protected from vandals and severe weather.

FAST INSTALLATION

This compact ductless system is simple to install. Only wires and piping need to run between the indoor and outdoor units. These units are fast and easy to install ensuring minimal disruption to customers in homes or the workplace. This makes these systems the equipment of choice for retrofit applications.

SIMPLE SERVICING AND MAINTENANCE

Removing the top panel of the outdoor unit provides immediate access to the control compartment, providing the service technician access to the diagnostic LEDs to facilitate the troubleshooting process. In addition, the draw-thru design of the outdoor unit means that dirt accumulates on the outside surface of the coil. Coils can be cleaned quickly from the inside using a pressure hose and detergent.

On the indoor units, service and maintenance expense is reduced due to the permanent easy to clean filters. Also, error codes are displayed on the front panel to alert the user to certain system malfunctions

BUILT-IN RELIABILITY

Ductless system indoor and outdoor units are designed to provide years of trouble-free operation.

Both the indoor and outdoor units are well protected. Whenever the microprocessor detects abnormal conditions, the unit stops and an error code appears.


Inverter systems provide additional reliability due to the soft start. This refers to the ability of the inverter to start the compressor motor using reduced voltage and reduced current. This feature is beneficial from an electrical standpoint (eliminates current spikes) as well as an overall reliability standpoint due to reduced stress on all associated system components.

AGENCY LISTINGS

All systems are listed with AHRI (Air conditioning, Heating, and Refrigeration Institute) and are ETL certified per UL 1995 standard.

MODEL NUMBER NOMENCLATURE

OUTDOOR UNIT



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.



STANDARD FEATURES AND ACCESSORIES

Ease Of Installation	
Low Voltage Controls	S
Comfort Features	
Microprocessor Controls	S
Auto Restart Function	S
Auto Changeover	S
Energy Saving Features	
Inverter Driven Compressor	S
46°F Heating Mode (Heating Setback)	S
Safety And Reliability	
3 Minute Time Delay For Compressor	S
High Compressor Discharge Temperature	S
Low Voltage Protection	S
Compressor Overload Protection	S
Compressor Over Current Protection	S
IPM Module Protection	S
Condenser High Temp Protection in Cooling Mode	S
Aluminum Golden Hydrophilic pre-coated fins	S
Ease Of Service And Maintenance	
Diagnostics	S
Liquid Line Pressure Taps	S
Application Flexibility	
Crankcase Heater	S
Base Pan Heater (Heat Pumps)	S

Legend
 S Standard
 A Accessory

ACCESSORIES

Outdoor Unit Model Number	Basepan Base Rubber Plugs RCD Part Number	Quantity per unit
DLCERAA12AAJ	12600801A00077	12
DLCERAA12AAK		
DLCERAA18AAK		
DLCERAA24AAK		25
DLCERAH12AAJ		12
DLCERAH09AAK		
DLCERAH12AAK		
DLCERAH18AAK		
DLCERAH24AAK		

NOTE: Basepan is built-in with multiple holes for proper draining during defrost. For applications where it is required to seal these holes and redirect the condensate drain, rubber plugs are available through RCD.

OUTDOOR UNITS

Crankcase Heater

The crankcase heater is standard on all unit sizes. Heater clamps must be placed around the compressor oil stump.

BASE PAN HEATER

The base pan heater is standard on all unit sizes (Heat Pump models only).

DIMENSIONS

	System Size		Height (H) in. (mm)	Width (W) in. (mm)	Depth (D) in. (mm)	Weight—Net lbs. (kg)
	Cooling Only	12K	(115V)	21.85(555)	30.31(770)	11.81(300)
12K		(208/230V)	21.85(555)	30.31(770)	11.81(300)	53.8(24.4)
18K		(208/230V)	21.81(554)	31.50(800)	13.11(333)	70.1(31.8)
24K		(208/230V)	27.64(702)	33.27(845)	14.29(363)	88.6(40.2)
	System Size		Height (H) in. (mm)	Width (W) in. (mm)	Depth (D) in. (mm)	Weight—Net lbs. (kg)
	Heat Pump	12K	(115V)	21.85(555)	30.31(770)	11.81(300)
9K		(208/230V)	21.85(555)	30.31(770)	11.81(300)	63.0(28.6)
12K		(208/230V)	21.85(555)	30.31(770)	11.81(300)	65.5(29.7)
18K		(208/230V)	21.81(554)	31.50(800)	13.11(333)	79.6(36.1)
24K		(208/230V)	27.64(702)	33.27(845)	14.29(363)	114.2(51.8)





Fig. 1 – Sizes 9K and 12K


DIMENSIONS (CONT)



Unit: inch(mm)

Fig. 2 – Size 18K


DIMENSIONS (CONT)



Unit: inch (mm)

Fig. 3 – Size 24K

CLEARANCES



A07894

Fig. 4 – Outdoor Unit Clearance

UNIT	MINIMUM VALUE in(mm)
A	24 (610)
B	24 (610)
C	24 (610)
D	4 (101)
E	4 (101)

NOTE: The outdoor unit must be mounted at least 2in. (50mm) above the maximum anticipated snow depth.




Fig. 5 – Clearance for Multiple Units

SPECIFICATIONS

SPECIFICATIONS – OUTDOOR COOLING ONLY

COOLING ONLY							
System	Size		12K	12K	18K	24K	
		Outdoor Model		DLCERAA12AAJ	DLCERAA12AAK	DLCERAA18AAK	DLCERAA24AAK
Electrical	Voltage, Phase, Cycle		V/Ph/Hz	115–1–60	208/230–1–60	208/230–1–60	208/230–1–60
	MCA	A.	13	7	11	16	
	MOCP – Fuse Rating	A.	20	15	15	25	
Operating	Cooling Outdoor DB Min – Max		° F(° C)	0~ 122 (-17~ 50)	0~ 122 (-17~ 50)	0~ 122 (-17~ 50)	0~ 122 (-17~ 50)
Piping	Total Piping Length		ft (m)	82 (25)	82 (25)	98 (30)	164 (50)
	Piping Lift*		ft (m)	33 (10)	33 (10)	66 (20)	66 (20)
	Pipe Connection Size – Liquid		In.(mm)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	3/8 (9.52)
	Pipe Connection Size – Suction		In.(mm)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	5/8 (16)
Refrigerant	Type		R410A	R410A	R410A	R410A	
	Charge	lbs (kg)	1.30 (0.59)	1.30 (0.59)	2.09 (0.95)	2.64 (1.20)	
	Metering Device		EEV	EEV	EEV	EEV	
Outdoor Coil	Face Area		Sq. Ft.	4.15	4.15	4.78	4.78
	No. Rows			1	1	2	2
	Fins per inch			22	22	22	22
	Circuits			2	2	4	6
Compressor	Type		Rotary Inverter	Rotary Inverter	Rotary Inverter	Rotary Inverter	
	Model		ASN98D22UFZ	ASN98D22UFZ	ASM135D23UFZ	ATF235D22UMT	
	Oil Type		VG74	VG74	VG74	VG74	
	Oil Charge	Fl. Oz.	13.0	13.0	13.0	23.6	
	Rated Current	RLA	9.5	4.5	7.0	11.0	
Outdoor	Unit Width		In.(mm)	30.31(770)	30.31(770)	31.50(800)	33.27(845)
	Unit Height		In.(mm)	21.85(555)	21.85(555)	21.81(554)	27.64(702)
	Unit Depth		In.(mm)	11.81(300)	11.81(300)	13.11(333)	14.29(363)
	Net Weight		lbs (kg)	57.8(26.2)	53.8(24.4)	70.1(31.8)	88.6(40.2)
	Airflow		CFM	1,170	1,170	1,170	1,880
	Sound Pressure		dB(A)	52.0	54.0	57.0	59.5

* Condensing unit above or below the indoor unit

COMPATIBILITY

INDOOR UNIT		OUTDOOR UNIT			
		DLCERAA12AAJ	DLCERAA12AAK	DLCERAA18AAK	DLCERAA24AAK
HIGH WALL	DLFEHAA12XAJ	•			
	DLFEHAA12XAK		•		
	DLFEHAA18XAK			•	
	DLFEHAA24XAK				•

PERFORMANCE

HIGH WALL	Indoor Model		DLFEHAA12XAJ	DLFEHAA12XAK	DLFEHAA18XAK	DLFEHAA24XAK
	Energy Star		NO	NO	NO	NO
	Cooling System Tons		1.0	1.0	1.5	2.0
	Cooling Rated Capacity	Btu/h	12,000	12,000	18,000	24,000
	Cooling Cap. Range Min – Max	Btu/h	4800~13200	4800~13000	5800~18600	9400~25200
	SEER		16.8	16.0	16.5	17.0
	EER		10.7	11.2	10.3	10.9

SPECIFICATIONS (CONT)

SPECIFICATIONS – OUTDOOR HEAT PUMP

		HEAT PUMP					
System	Size		12	9	12	18	24
	Outdoor Model		DLCERAH12AAJ	DLCERAH09AAK	DLCERAH12AAK	DLCERAH18AAK	DLCERAH24AAK
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	115–1–60	208/230–1–60	208/230–1–60	208/230–1–60	208/230–1–60
	MCA	A.	13	8	10	15	18
	MOCP – Fuse Rating	A.	20	15	15	20	25
Operating Range	Cooling Outdoor DB Min – Max	° F(° C)	0~122 (-17~50)	0~122 (-17~50)	0~122 (-17~50)	0~122 (-17~50)	0~122 (-17~50)
	Heating Outdoor DB Min – Max	° F(° C)	0~86 (-17~30)	0~86 (-17~30)	0~86 (-17~30)	0~86 (-17~30)	0~86 (-17~30)
Piping	Total Piping Length	ft (m)	82 (25)	82 (25)	82 (25)	98 (30)	164 (50)
	Piping Lift*	ft (m)	33 (10)	33 (10)	33 (10)	66 (20)	66 (20)
	Pipe Connection Size – Liquid	In.(mm)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	3/8 (9.52)
	Pipe Connection Size – Suction	In.(mm)	1/2 (12.7)	3/8 (9.52)	1/2 (12.7)	1/2 (12.7)	5/8 (16)
Refrigerant	Type		R410A	R410A	R410A	R410A	R410A
	Charge	lbs (kg)	2.11 (0.96)	1.76 (0.80)	2.11 (0.96)	2.82 (1.28)	3.97 (1.80)
	Metering Device		EEV	EEV	EEV	EEV	EEV
Outdoor Coil	Face Area	Sq. Ft.	4.1	4.1	4.1	4.7	5.3
	No. Rows		1.5	1	1.5	2	2
	Fins per inch		18	18	18	18	18
	Circuits		4	2	4	4	4
Compressor	Type		Rotary Inverter	Rotary Inverter	Rotary Inverter	Rotary Inverter	Rotary Inverter
	Model		ASN98D22UFZ	ASN98D22UFZ	ASN98D22UFZ	ASM135D23UFZ	ATF235D22UMT
	Oil Type		VG74	VG74	VG74	VG74	VG74
	Oil Charge	Fl. Oz.	13.0	13.0	13.0	15.8	23.6
	Rated Current	RLA	9.5	5.5	6.8	10.5	12.0
Outdoor	Unit Width	In.(mm)	30.31(770)	30.31(770)	30.31(770)	31.50(800)	33.27(845)
	Unit Height	In.(mm)	21.85(555)	21.85(555)	21.85(555)	21.81(554)	27.64(702)
	Unit Depth	In.(mm)	11.81(300)	11.81(300)	11.81(300)	13.11(333)	14.29(363)
	Net Weight	lbs (kg)	69.0(31.3)	63(28.6)	65.5(29.7)	79.6(36.1)	114.2(51.8)
	Airflow	CFM	1,170	1,170	1,170	1,170	1,765
	Sound Pressure	dB(A)	54.5	57.2	57.4	57.0	60.2

* Condensing unit above or below the indoor unit

COMPATIBILITY

INDOOR UNIT		OUTDOOR UNIT				
		DLCERAH12AAJ	DLCERAH09AAK	DLCERAH12AAK	DLCERAH18AAK	DLCERAH24AAK
HIGH WALL	DLFEHAH12XAJ	•				
	DLFEHAH09XAK		•			
	DLFEHAH12XAK			•		
	DLFEHAH18XAK				•	
	DLFEHAH24XAK					•

PERFORMANCE

HIGH WALL	Indoor Model		DLFEHAH12XAJ	DLFEHAH09XAK	DLFEHAH12XAK	DLFEHAH18XAK	DLFEHAH24XAK
	Energy Star		NO	NO	NO	NO	NO
	Cooling System Tons		1.0	0.8	1.0	1.5	2.0
	Cooling Rated Capacity	Btu/h	12,000	9,000	12,000	18,000	24,000
	Cooling Cap. Range Min – Max	Btu/h	3,700~13,000	3,400~10,500	3,700~13,000	5,500~19,000	8,987~26,585
	SEER		17.3	17.6	17.5	17.5	16.9
	EER		10	11.2	11.2	11.2	9.7
	Heating Rated Capacity (47° F)	Btu/h	12,000	9,800	12,000	18,000	24,800
	Heating Rated Capacity (17° F)	Btu/h	8,000	7,500	9,230	11,600	18,000
	Heating Maximum Capacity (17° F)	Btu/h	8,000	8,530	9,830	11,950	19,750
	Heating Maximum Capacity (5° F)	Btu/h	9,000	6,070	8,880	10,150	16,760
	Heating Cap. Range Min – Max	Btu/h	3,500~13,500	2,800~11,500	3,500~13,500	6,200~19,000	8,371~25,350
	HSPF		10.6	10.0	9.6	10.6	9.6
	COP (47° F)	W/W	2.93	3.27	3.22	3.26	3.13
	COP (17° F)	W/W	2.58	2.58	2.64	2.64	2.49
COP (5° F)	W/W	1.60	1.60	1.60	1.50	1.40	

COOLING PERFORMANCE DATA – (COOLING ONLY)

Model	Cooling		Outdoor conditions (DB)										
	Indoor Conditions DB			0F	5F	17F	47F	77F	86F	95F	104F	113F	122F
	DB	WB		(-17C)	(-15C)	(-8C)	(8C)	(25C)	(30C)	(35C)	(40C)	(45C)	(50C)
12 (115V)	69.8F (21C)	59F (15C)	TC	6.54	6.67	7.33	8.42	8.57	11.44	9.94	8.98	7.80	4.84
			SC	5.60	5.77	6.08	6.20	6.32	7.72	6.98	6.53	6.00	4.67
			Input	0.21	0.21	0.25	0.30	0.56	1.16	1.03	1.04	1.03	0.80
	75.2F (24C)	62.6F (17C)	TC	6.99	7.13	7.84	9.01	9.24	12.18	10.66	9.67	8.41	5.43
			SC	6.00	6.19	6.51	6.64	6.83	8.16	7.46	7.03	6.48	5.24
			Input	0.20	0.21	0.24	0.30	0.56	1.19	1.06	1.06	1.05	0.81
	80.6F (27C)	66.2F (19C)	TC	7.46	7.61	8.36	9.61	10.94	12.99	12.32	10.26	9.06	5.97
			SC	6.36	6.56	6.90	7.04	7.30	8.60	7.88	7.43	6.94	4.72
			Input	0.20	0.21	0.24	0.30	0.56	1.22	1.08	1.08	1.07	0.81
	89.6F (32C)	73.4F (23C)	TC	12.04	12.28	13.50	15.52	14.21	14.69	12.90	11.76	10.47	7.13
			SC	8.20	8.45	8.89	9.07	8.68	8.85	8.19	7.79	7.34	6.20
			Input	0.56	0.57	0.67	0.81	0.94	1.28	1.14	1.13	1.10	0.83
12 (208-230V)	69.8F (21C)	59F (15C)	TC	7.16	7.31	8.03	9.23	8.72	8.75	9.83	8.31	7.07	4.56
			SC	6.21	6.40	6.74	6.87	6.70	6.71	7.24	6.48	5.89	4.56
			Input	0.31	0.32	0.37	0.45	0.59	0.73	1.10	1.02	1.01	0.79
	75.2F (24C)	62.6F (17C)	TC	7.64	7.80	8.57	9.85	9.58	11.84	10.69	9.07	7.76	5.02
			SC	6.63	6.83	7.19	7.34	7.26	8.32	7.80	7.07	6.43	5.02
			Input	0.31	0.32	0.38	0.46	0.60	1.12	1.12	1.03	1.02	0.79
	80.6F (27C)	66.2F (19C)	TC	8.16	8.33	9.15	10.52	11.25	12.71	11.98	9.76	8.45	5.59
			SC	7.03	7.25	7.63	7.78	7.55	8.79	8.37	7.56	6.94	5.59
			Input	0.32	0.33	0.39	0.47	0.56	1.15	1.15	1.04	1.03	0.80
	89.6F (32C)	73.4F (23C)	TC	11.49	11.72	12.88	14.80	14.83	14.65	13.37	11.35	9.92	6.56
			SC	8.37	8.63	9.08	9.27	9.28	9.26	8.80	8.04	7.41	6.18
			Input	0.73	0.75	0.88	1.07	1.07	1.22	1.22	1.09	1.07	0.81
18 (208-230V)	69.8F (21C)	59F (15C)	TC	7.85	11.21	12.32	14.16	15.32	17.55	15.92	13.84	11.90	7.57
			SC	6.86	9.80	10.32	10.53	10.16	12.14	11.37	10.38	9.52	7.34
			Input	0.26	0.40	0.46	0.57	0.80	1.63	1.59	1.48	1.47	1.15
	75.2F (24C)	62.6F (17C)	TC	7.29	10.41	11.44	13.15	14.28	18.35	16.97	14.93	13.03	8.51
			SC	6.75	9.64	10.15	10.36	10.91	12.73	12.10	11.18	10.36	8.27
			Input	0.21	0.33	0.38	0.47	0.80	1.65	1.62	1.52	1.49	1.16
	80.6F (27C)	66.2F (19C)	TC	7.38	10.55	11.59	13.32	15.17	18.99	18.15	15.98	14.10	9.36
			SC	6.85	9.79	10.31	10.52	11.60	13.18	12.69	11.92	11.17	9.16
			Input	0.21	0.33	0.38	0.46	0.81	1.69	1.65	1.55	1.52	1.17
	89.6F (32C)	73.4F (23C)	TC	7.41	10.59	11.64	13.38	19.66	19.99	18.99	17.42	15.97	11.05
			SC	6.52	9.32	9.81	10.01	12.92	13.07	12.70	12.14	11.65	10.14
			Input	0.21	0.33	0.38	0.46	1.41	1.71	1.69	1.60	1.57	1.19
24 (208-230V)	69.8F (21C)	59F (15C)	TC	15.64	15.96	17.54	20.16	22.14	24.70	22.98	21.84	18.64	15.25
			SC	13.33	13.75	14.47	14.77	15.55	16.90	16.00	15.46	13.86	12.45
			Input	0.69	0.71	0.83	1.01	1.68	2.54	2.56	2.77	2.57	2.38
	75.2F (24C)	62.6F (17C)	TC	16.64	16.98	18.66	21.45	22.46	25.97	24.36	23.34	20.30	15.40
			SC	14.17	14.61	15.38	15.69	16.13	17.79	17.06	16.52	15.11	13.01
			Input	0.71	0.73	0.85	1.03	1.54	2.58	2.60	2.82	2.63	2.22
	80.6F (27C)	66.2F (19C)	TC	17.62	17.98	19.75	22.70	23.55	27.04	25.57	24.49	21.09	15.40
			SC	14.96	15.42	16.23	16.56	16.88	18.44	17.80	17.35	15.88	13.52
			Input	0.72	0.74	0.86	1.05	1.55	2.61	2.63	2.87	2.57	2.07
	89.6F (32C)	73.4F (23C)	TC	19.18	19.57	21.50	24.72	28.40	28.70	27.34	26.59	22.98	18.01
			SC	15.19	15.66	16.48	16.82	18.15	18.26	17.76	17.51	16.18	14.41
			Input	0.73	0.75	0.87	1.07	2.25	2.67	2.69	2.94	2.53	2.13

LEGEND
 DB - Dry Bulb
 WB - Wet Bulb
 TC - Total Net Capacity (1000BTU/hour)
 SC - Sensible Capacity (1000BTU/hour)
 Input - Total Power (kW)

COOLING PERFORMANCE DATA – (HEAT PUMP)

Model	Cooling			Outdoor Conditions (DB)									
	Indoor Conditions			0F	5F	17F	47F	77F	86F	95F	104F	113F	122F
	DB	WB		(-17C)	(-15C)	(-8C)	(8C)	(25C)	(30C)	(35C)	(40C)	(45C)	(50C)
12 (115V)	69.8F (21C)	59F (15C)	TC	11.24	11.44	11.38	10.68	10.82	10.99	10.45	9.73	7.88	4.96
			SC	7.73	7.85	7.86	7.42	7.46	7.67	7.39	7.06	6.26	4.94
			Input	0.48	0.46	0.43	0.46	0.45	0.90	0.97	1.06	1.00	0.81
	75.2F (24C)	62.6F (17C)	TC	12.25	12.11	12.18	11.43	11.63	11.90	11.21	10.29	8.30	5.44
			SC	8.33	8.34	8.31	7.99	8.05	8.18	7.85	7.45	6.58	5.41
			Input	0.46	0.50	0.46	0.48	0.46	0.91	0.99	1.04	0.96	0.81
	80.6F (27C)	66.2F (19C)	TC	12.93	12.61	11.40	11.44	11.00	11.98	12.01	11.24	9.32	6.03
			SC	8.71	8.80	8.76	8.32	8.17	8.67	8.46	8.16	7.32	6.10
			Input	0.49	0.52	0.47	0.42	0.61	0.92	1.19	1.10	1.00	0.82
	89.6F (32C)	73.4F (23C)	TC	14.54	14.30	14.73	14.62	13.29	13.05	12.97	12.52	10.31	7.51
			SC	9.03	8.99	9.11	9.58	8.61	8.55	8.52	8.33	7.48	6.58
			Input	0.58	0.61	0.55	0.81	0.84	0.93	1.03	1.09	0.93	0.83
09 (208–230V)	69.8F (21C)	59F (15C)	TC	9.06	8.57	7.95	9.11	9.16	8.79	9.42	6.98	6.52	5.08
			SC	6.56	6.61	5.88	7.47	7.60	6.91	7.22	4.88	4.53	3.01
			Input	0.38	0.40	0.40	0.62	0.76	0.90	1.19	1.00	0.93	0.95
	75.2F (24C)	62.6F (17C)	TC	9.59	9.30	8.60	10.07	9.83	9.76	10.17	8.17	6.70	5.76
			SC	6.18	6.15	5.73	6.50	6.41	6.37	6.55	5.66	5.01	4.65
			Input	0.41	0.43	0.43	0.63	0.73	0.90	1.19	1.01	0.94	0.96
	80.6F (27C)	66.2F (19C)	TC	10.20	9.91	9.81	11.17	11.31	11.56	10.78	8.41	6.95	6.10
			SC	6.59	6.53	7.01	7.50	7.69	7.58	6.96	5.91	5.26	5.10
			Input	0.48	0.46	0.47	0.51	0.73	0.95	1.20	1.06	0.98	1.01
	89.6F (32C)	73.4F (23C)	TC	11.39	11.15	10.81	12.39	13.39	12.26	12.12	9.24	8.03	6.74
			SC	6.83	6.75	6.88	7.23	7.83	7.17	7.15	6.02	5.57	5.08
			Input	0.52	0.56	0.57	1.04	1.01	0.92	1.23	1.03	0.96	0.97
12 (208–230V)	69.8F (21C)	59F (15C)	TC	12.24	11.97	12.09	12.05	11.58	12.11	11.93	10.59	8.17	7.18
			SC	8.47	8.38	8.37	8.32	8.08	8.32	8.24	7.63	6.41	5.97
			Input	0.58	0.53	0.37	0.66	1.02	1.10	1.27	1.24	0.95	0.97
	75.2F (24C)	62.6F (17C)	TC	13.26	13.53	12.36	12.45	12.18	12.91	12.67	10.78	8.67	7.73
			SC	9.10	9.19	8.60	8.63	8.52	8.86	8.68	7.89	6.88	6.49
			Input	0.71	0.71	0.46	0.67	0.76	1.10	1.29	1.24	0.95	0.98
	80.6F (27C)	66.2F (19C)	TC	13.82	14.07	14.91	12.71	12.95	13.75	13.49	11.07	9.20	8.05
			SC	9.44	9.50	9.90	8.84	8.98	9.29	9.12	8.14	7.07	6.80
			Input	0.72	0.73	0.69	0.68	0.76	1.11	1.30	1.25	0.96	0.98
	89.6F (32C)	73.4F (23C)	TC	14.89	15.18	15.53	14.36	16.88	15.79	14.92	11.84	10.34	8.68
			SC	9.54	9.61	9.70	9.22	10.20	9.71	9.41	8.24	7.68	7.07
			Input	0.75	0.76	0.70	1.03	1.11	1.78	1.33	1.26	0.97	0.99
18 (208–230V)	69.8F (21C)	59F (15C)	TC	19.82	18.50	18.02	15.81	17.95	17.37	17.66	16.59	11.76	10.12
			SC	13.87	12.96	12.85	11.15	12.96	12.35	13.74	12.99	10.86	10.07
			Input	0.76	0.77	0.80	0.67	0.87	1.42	1.75	1.83	1.39	1.43
	75.2F (24C)	62.6F (17C)	TC	20.51	19.26	18.68	16.45	18.46	18.38	18.22	17.94	12.61	10.95
			SC	14.57	14.02	14.52	12.71	13.90	13.70	14.06	13.89	11.87	10.95
			Input	0.80	0.81	0.85	0.71	0.92	1.48	1.81	1.90	1.42	1.49
	80.6F (27C)	66.2F (19C)	TC	21.52	20.35	19.74	18.38	19.20	19.60	19.14	18.94	13.85	11.94
			SC	15.51	15.74	16.22	14.81	15.00	14.89	15.32	14.84	13.10	11.94
			Input	0.85	0.86	0.89	0.76	0.96	1.52	1.85	1.95	1.48	1.54
	89.6F (32C)	73.4F (23C)	TC	22.49	21.22	20.38	20.43	22.59	23.55	22.15	21.37	15.67	13.48
			SC	15.32	15.11	16.66	14.82	15.96	15.01	15.72	15.23	13.79	13.00
			Input	0.96	0.98	1.26	1.25	1.18	1.52	1.89	1.99	1.49	1.55
24 (208–230V)	69.8F (21C)	59F (15C)	TC	25.25	25.18	25.21	24.09	23.85	24.10	22.92	20.08	14.76	9.91
			SC	17.91	17.81	17.82	16.77	16.60	16.74	16.04	15.19	12.06	7.78
			Input	1.75	1.80	1.72	1.32	1.60	2.43	2.65	2.52	2.10	1.79
	75.2F (24C)	62.6F (17C)	TC	27.07	27.34	28.29	25.45	25.50	26.45	24.08	21.05	15.76	10.53
			SC	18.94	18.59	19.58	17.90	17.56	18.47	16.85	15.89	11.53	7.55
			Input	1.84	1.83	1.75	1.42	1.62	2.46	2.70	2.56	2.12	1.79
	80.6F (27C)	66.2F (19C)	TC	29.21	29.96	30.18	27.10	26.80	27.93	24.93	22.19	16.55	13.08
			SC	20.47	21.03	21.41	19.08	18.82	19.88	18.08	16.04	12.05	9.79
			Input	1.89	1.91	1.78	1.46	1.66	2.48	2.66	2.58	2.13	1.80
	89.6F (32C)	73.4F (23C)	TC	31.19	31.10	31.10	27.86	30.22	30.43	28.05	24.84	18.36	14.88
			SC	21.92	21.99	21.85	19.63	21.48	21.78	19.85	18.75	13.58	11.05
			Input	1.92	2.07	1.91	1.61	2.02	2.55	2.82	2.65	2.17	1.82

LEGEND
 DB - Dry Bulb
 WB - Wet Bulb
 TC - Total Net Capacity (1000BTU/hour)
 SC - Sensible Capacity (1000BTU/hour)
 Input - Total Power (kW)

HEATING PERFORMANCE DATA – (HEAT PUMP)

Model	Heating Indoor Conditions DB		Outdoor Conditions (DB)								
			0F (-17C)	5F (-15C)	17F (-8C)	19.4F (-7C)	24.8F (-4C)	32F (0C)	39.2F (4C)	44.6F (7C)	53.6F (12C)
12 (115V)	59F (15C)	TC	5.65	6.37	7.89	8.78	9.55	10.55	11.46	12.45	12.89
		Input	0.82	0.88	0.90	0.92	0.99	0.99	1.15	1.21	1.01
		COP	2.03	2.11	2.57	2.79	2.84	3.11	2.92	3.01	3.73
	64.4F (18C)	TC	5.45	5.17	6.69	7.58	8.35	9.35	11.26	12.11	12.84
		Input	0.80	0.86	0.88	0.90	0.97	0.97	1.20	1.24	1.06
		COP	2.01	1.76	2.23	2.46	2.53	2.82	2.75	2.87	3.54
	69F (20.5C)	TC	5.25	4.37	5.89	6.78	7.55	8.55	11.16	12.03	12.75
		Input	0.78	0.84	0.86	0.88	0.95	0.95	1.21	1.26	1.07
		COP	1.98	1.52	2.01	2.25	2.34	2.63	2.70	2.80	3.48
	71.6F (22C)	TC	5.20	6.32	7.56	8.54	9.51	10.21	10.99	11.88	12.49
		Input	0.84	0.81	0.85	0.87	1.00	0.90	1.03	1.10	1.10
		COP	1.81	2.28	2.61	2.87	2.80	3.32	3.12	3.18	3.33
09 (208-230V)	59F (15C)	TC	7.28	7.70	8.53	9.43	10.05	10.45	11.33	11.92	12.68
		Input	1.17	1.14	1.15	1.17	1.03	0.94	0.95	1.02	1.12
		COP	1.82	1.99	2.17	2.35	2.85	3.26	3.49	3.44	3.32
	64.4F (18C)	TC	6.08	6.50	7.33	8.23	8.85	9.85	11.13	11.72	12.48
		Input	1.15	1.12	1.13	1.15	1.01	0.92	1.00	1.07	1.17
		COP	1.55	1.71	1.90	2.09	2.56	3.14	3.25	3.22	3.12
	69F (20.5C)	TC	5.28	5.70	6.53	7.43	8.05	9.05	10.03	11.63	12.38
		Input	1.13	1.10	1.11	1.13	0.99	0.90	1.01	1.08	1.18
		COP	1.37	1.52	1.72	1.92	2.38	2.95	2.90	3.16	3.07
	71.6F (22C)	TC	6.43	6.95	7.68	8.58	8.90	9.30	10.14	11.13	12.29
		Input	1.06	1.03	1.20	1.23	1.08	0.98	1.02	1.09	1.19
		COP	1.78	1.99	1.87	2.05	2.42	2.78	2.90	3.00	3.02
12 (208-230V)	59F (15C)	TC	7.91	8.89	9.84	10.87	11.11	11.35	11.86	12.41	13.00
		Input	0.83	1.27	0.81	1.37	0.90	1.01	1.17	1.51	1.04
		COP	2.79	2.06	3.54	2.32	3.61	3.30	2.98	2.41	3.66
	64.4F (18C)	TC	6.33	7.65	8.06	9.56	9.83	10.53	11.38	12.03	12.74
		Input	0.85	0.82	0.84	0.86	0.92	0.83	1.19	1.53	1.51
		COP	2.18	2.74	2.83	3.26	3.12	3.72	2.81	2.31	2.47
	69F (20.5C)	TC	5.55	6.07	6.98	8.08	8.95	10.55	12.20	13.65	14.06
		Input	0.88	0.84	0.86	0.88	0.95	0.85	1.21	1.55	1.54
		COP	1.86	2.11	2.38	2.69	2.78	3.63	2.96	2.58	2.68
	71.6F (22C)	TC	4.58	5.35	5.95	7.12	7.92	8.94	10.48	11.52	12.38
		Input	0.86	0.79	0.84	0.86	0.93	0.98	1.20	1.54	1.16
		COP	1.56	1.99	2.07	2.42	2.50	2.67	2.57	2.20	3.14
18 (208-230V)	59F (15C)	TC	9.03	10.16	11.43	12.37	13.33	14.90	16.83	18.03	18.59
		Input	2.33	5.12	2.12	5.25	1.92	5.03	1.71	1.61	5.06
		COP	1.14	1.99	1.58	2.36	2.04	2.26	2.88	3.29	3.68
	64.4F (18C)	TC	8.55	10.05	11.95	12.45	13.45	15.65	16.85	18.15	18.17
		Input	2.35	2.25	2.15	2.04	1.94	1.84	1.73	1.63	1.62
		COP	1.07	1.31	1.63	1.79	2.03	2.50	2.85	3.26	3.29
	69F (20.5C)	TC	8.47	9.67	11.87	12.47	13.37	15.57	16.87	18.07	18.09
		Input	2.37	2.27	2.17	2.07	1.96	1.86	1.76	1.65	1.64
		COP	1.05	1.25	1.61	1.77	2.00	2.46	2.82	3.20	3.23
	71.6F (22C)	TC	7.85	8.78	11.25	12.50	13.35	14.74	16.85	18.05	18.18
		Input	2.36	5.02	2.15	5.47	1.95	5.41	1.74	1.64	5.52
		COP	0.98	1.75	1.53	2.29	2.01	2.72	2.84	3.23	3.29

HEATING PERFORMANCE DATA – (HEAT PUMP) (CONT)

Model	Heating Indoor Conditions DB		Outdoor Conditions (DB)								
			0F (-17C)	5F (-15C)	17F (-8C)	19.4F (-7C)	24.8F (-4C)	32F (0C)	39.2F (4C)	44.6F (7C)	53.6F (12C)
24 (208–230V)	59F (15C)	TC	14.08	16.77	19.76	21.26	23.01	24.12	25.70	26.17	26.60
		Input	2.60	2.88	2.76	2.83	2.62	2.44	2.47	2.33	2.82
		COP	1.59	1.71	2.10	2.10	2.57	2.08	3.05	3.29	3.00
	64.4F (18C)	TC	13.36	15.13	19.00	21.27	22.02	23.36	24.43	25.67	26.69
		Input	2.83	3.08	2.88	2.74	2.68	2.72	2.58	2.43	2.25
		COP	1.38	1.44	1.93	2.27	2.41	2.52	2.78	3.10	3.47
	69F (20.5C)	TC	12.60	14.92	18.50	20.79	21.22	22.45	23.69	24.52	25.29
		Input	2.89	3.17	2.92	2.83	2.77	2.83	2.66	2.52	2.43
		COP	1.28	1.38	1.86	2.15	2.25	2.32	2.61	2.85	3.05
	71.6F (22C)	TC	11.87	15.37	19.07	21.85	22.82	23.37	24.48	25.44	27.45
		Input	2.98	2.75	3.25	2.82	2.95	2.68	2.81	2.88	2.88
		COP	1.17	1.64	1.72	2.27	2.27	2.56	2.55	2.59	2.79

LEGEND
 DB - Dry Bulb
 WB - Wet Bulb
 TC - Total Net Capacity (1000BTU/hour)
 Input - Total Power (kW)
 COP -W/W

APPLICATION DATA

UNIT SELECTION

Select equipment that either matches or supports slightly more than the anticipated peak load. This provides better humidity control, fewer unit cycles, and less part-load operation.

For units used in spaces with high sensible loads, base equipment selection on unit sensible load, not on total anticipated load. Adjust for anticipated room wet bulb temperature to avoid undersizing the equipment.

UNIT MOUNTING (OUTDOOR)

Refer to the unit's installation instructions for further details.

Unit leveling – For reliable operation, units should be level in all planes.

Clearance – Minimum clearance (see Fig. 4) must be provided for airflow. The condensing units are designed for free-flow application. Air inlets and outlets should not be restricted.

Unit location – A location which is convenient to installation and not exposed to strong winds. A location that can bear the weight of the outdoor unit and where the outdoor unit can be mounted in a level position.

Do not install the indoor or outdoor units in a location with special environmental conditions. For those applications, contact your sales representative.

SYSTEM OPERATING CONDITIONS

OPERATING RANGE MIN / MAX °F (°C)		
	COOLING	HEATING
OUTDOOR DB	0 ~ 122 (-17 ~ 50)	0 ~ 86 (-17 ~ 30)

NOTE: Reference the product installation instructions for more information.

METERING DEVICES

The outdoor unit has an electronic expansion valve to manage the refrigerant flow of the connected fan coil.

DRAIN CONNECTIONS

Install drains to meet the local sanitation codes.

REFRIGERANT LINES

General refrigerant line sizing:

- The outdoor units are shipped with a full charge of R410A refrigerant. All charges, line sizing, and capacities are based on runs of 25ft. (7.6m). For runs over 25ft. (7.6m), review the *Long Line Applications* section for the proper charge adjustments.
- Refrigerant lines should not be buried in the ground. If it is necessary to bury the lines, do not bury more than 36in (914mm). Provide a minimum 6in (152mm) vertical rise to the service valves to prevent refrigerant migration.
- Both lines must be insulated. Use a minimum of 1/2in. (12.7mm) thick insulation. Closed-cell insulation is recommended in all long-line applications.
- Special consideration should be given to isolating the interconnecting tubing from the building structure. Isolate the tubing so vibration or noise is not transmitted into the structure.

Long Line Applications:

- No change in line sizing is required.
- Add refrigerant per the Additional Charge table.

ADDITIONAL CHARGE						
UNIT SIZE	TOTAL LINE LENGTH ft. (m)		ADDITIONAL CHARGE, oz/ft. FT. (m)			
	Min	Max	10–25 (3–8)	>25–82 (8–25)	>82–98 (25–30)	>98–164 (30–50)
9	10(3)	82(25)	None	0.16		
12						
18		98(30)		0.16		
24		164(50)		0.32	0.32	0.32

WIRING

All wires must be sized per NEC (National Electrical Code) or CEC (Canadian Electrical Code) and local codes. Use Electrical Data table MCA (minimum circuit amps) and MOCP (maximum over current protection) to correctly size the wires and the disconnect fuse or breakers respectively.

Recommended Connection Method for Power and Communication Wiring:

The main power is supplied to the outdoor unit. The field supplied 14/3 stranded wire with ground with a 600 volt insulation rating, power/communication wiring from the outdoor unit to indoor unit consists of four (4) wires and provides the power for the indoor unit. Two wires are line voltage AC power, one is communication wiring (S) and the other is a ground wire. Wiring between indoor and outdoor unit is polarity sensitive. The use of BX wire is NOT recommended.

If installed in a high Electromagnetic field (EMF) area and communication issues exists, a 14/2 stranded shielded wire can be used to replace L2/N and (S) between outdoor unit and indoor unit landing the shield onto ground in the outdoor unit only.

CAUTION

EQUIPMENT DAMAGE HAZARD

Failure to follow this caution may result in equipment damage or improper operation.

Wires should be sized based on NEC and local codes.

Use copper conductors only with a 600 volt insulation rating wire.

CAUTION

EQUIPMENT DAMAGE HAZARD

Failure to follow this caution may result in equipment damage or improper operation.

Be sure to comply with local codes while running wire from the indoor unit to the outdoor unit.

Every wire must be connected firmly. Loose wiring may cause the terminal to overheat or result in unit malfunction. A fire hazard may also exist. Ensure all wiring is tightly connected.

No wire should touch the refrigerant tubing, compressor or any moving parts.

Disconnecting means must be provided and shall be located within sight and readily accessible from the air conditioner.

Connecting cable with conduit shall be routed through the hole in the conduit panel.

AIR FLOW DATA

COOLING ONLY				
Unit Size	12K (115V)	12K (208/230V)	18K (208/230V)	24K (208/230V)
Outdoor (CFM)	1170	1170	1170	1880

HEAT PUMP					
Unit Size	12K (115V)	9K (208/230V)	12K (208/230V)	18K (208/230V)	24K (208/230V)
Outdoor (CFM)	1170	1170	1170	1170	1765

SOUND DATA

COOLING ONLY					
Unit Size		12K (115V)	12K (208/230V)	18K (208/230V)	24K (208/230V)
Outdoor Sound Pressure Level	dB(A)	52	54	57	59.5
Outdoor Sound Power Level	dB(A)	63.3	63.9	65.9	66


HEAT PUMP						
Unit Size		12K (115V)	9K (208/230V)	12K (208/230V)	18K (208/230V)	24K (208/230V)
Outdoor Sound Pressure Level	dB(A)	54.5	57.2	57.4	57	60.2
Outdoor Sound Power Level	dB(A)	63.5	62.8	64.1	65.7	66.2

SOUND PRESSURE IN OCTAVE BANDS

COOLING ONLY										
	Frequency (Hz)	63	125	250	500	1000	2000	4000	6300	8000
12K (115)	Cooling dB(A)	60.2	57.3	52.0	49.9	45.9	41.1	35.6	30.1	60.2
	Indoor dB(A)	40.1	33.0	37.0	39.2	38.1	33.3	25.5	17.4	40.1
12K (208V)	Cooling dB(A)	54.0	59.1	53.8	54.2	49.8	42.0	36.3	30.9	54.0
	Indoor dB(A)	41.8	33.0	38.7	40.2	37.6	32.5	25.8	18.1	41.8
18K (208V)	Cooling dB(A)	63.8	66.7	58.8	54.6	52.5	48.0	43.4	36.1	63.8
	Indoor dB(A)	41.7	36.6	40.8	41.9	40.3	35.1	28.9	23.4	41.7
24K (208V)	Cooling dB(A)	58.8	64.1	59.2	55.0	52.0	47.5	44.6	39.5	58.8
	Indoor dB(A)	37.6	40.6	43.8	46.3	45.8	40.3	34.3	27.4	37.6

HEAT PUMP										
	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000	
12K (115)	Cooling dB(A)	52.6	56.9	56.6	53.3	48.7	42.1	37.4	34.0	
	Heating dB(A)	59.9	55.5	54.0	50.6	46.8	42.2	36.1	31.5	
	Indoor dB (A)	59.6	59.7	55.8	52.0	51.8	43.5	38.4	34.5	
9K (208V)	Cooling dB(A)	59.3	56.9	53.1	50.8	46.4	42.6	36.4	30.3	
	Heating dB(A)	57.8	56.3	55.1	51.7	47.9	44.5	38.7	33.6	
	Indoor dB (A)	62.7	63.3	56.3	53.1	49.9	46.6	40.3	33.2	
12K (208V)	Cooling dB(A)	64.8	57.3	55.7	53.3	51.1	48.1	42.6	36.1	
	Heating dB(A)	56.8	56.9	57.8	53.2	49.3	44.6	39.2	31.8	
	Indoor dB (A)	55.8	57.1	58.9	54.8	53.9	46.9	42.4	45.1	
18K (208V)	Cooling dB(A)	54.1	55.8	51.2	48.7	46.8	42.5	34.8	28.3	
	Heating dB(A)	52.9	58.6	51.7	49.9	50.3	43.0	38.5	33.3	
	Indoor dB (A)	56.0	54.7	52.4	50.2	46.7	40.8	34.2	27.0	
24K (208V)	Cooling dB(A)	52.6	56.9	56.6	53.3	48.7	42.1	37.4	34.0	
	Heating dB(A)	59.9	55.5	54.0	50.6	46.8	42.2	36.1	31.5	
	Indoor dB (A)	59.6	59.7	55.8	52.0	51.8	43.5	38.4	34.5	

OUTDOOR UNIT SOUND PRESSURE TEST CONDITIONS



NOTE: H=0.5 x Height of outdoor unit

	INDOOR CONDITION		OUTDOOR CONDITION	
	DB	WB	DB	WB
Cooling	80.6F (27C)	66.2F (19C)	95F (35C)	75.2F (24C)
Heating	68F (20C)	59F (15C)	44.6F (7C)	42.8F (6C)

ELECTRICAL DATA

	Outdoor Unit Size	12K	12K	18K	24K	
	Cooling Only	Volts–PH–Hz	(115V)	(208/230V)	(208/230V)	(208/230V)
		Max – Min* Oper. Voltage	127–104	253–187	253–187	253–187
Power Supply	MCA	7	7	11	16	
	MOCP	15	15	15	25	
Compressor	RLA	9.5	4.5	7	11	
	FLA	0.6	0.4	0.5	0.6	
Outdoor Fan Motor	Rated HP	0.054	0.054	0.065	0.068	
	Output	40	40	48	45	

	Outdoor Unit Size	12K	9K	12K	18K	24K	
	Heat Pump	Volts–PH–Hz	(115V)	(208/230V)	(208/230V)	(208/230V)	(208/230V)
		Max – Min* Oper. Voltage	127–104	253–187	253–187	253–187	253–187
Power Supply	MCA	13	8	10	15	18	
	MOCP	20	15	15	20	25	
Compressor	RLA	10.5	5.5	6.8	11.5	12	
	FLA	0.6	0.4	0.4	0.5	0.6	
Outdoor Fan Motor	Rated HP	0.054	0.054	0.054	0.054	0.068	
	Output	40	40	40	40	50	


*Permissible limits of the voltage range at which the unit will operate satisfactorily.

LEGEND

FLA – Full Load Amps
MCA – Minimum Circuit Amps
RLA – Rated Load Amps

WIRING DIAGRAMS (CONT)


Notes: -----
 This symbol indicates the element is optional, the actual shape shall prevail.



CODE	PART NAME	CODE	PART NAME
CN1A	Input: 220V high voltage connector with L/N/signal/ground	CN21	Input: temperature sensor connector (0~5V DC)
CN7	Output: 0~320V DC to connect DC FAN	CN25	Output: 0~220V AC to connect AC FAN
CN9~CN32	To connect PFC reactor	CN50	Output: 0~320V AC to connect compressor
CN17	Output: 220V AC to connect crankcase heater	CN60	Output: 0~220V AC to connect 4-way valve

Fig. 7 – Wiring Diagram – Sizes 09K, 12K (230V)

WIRING DIAGRAMS (CONT)



CODE	PART NAME	CODE	PART NAME
CN3	Input: 230V high voltage connector with L1/L2/signal/ground	CN5	Output: 0~220VAC to control AC FAN
CN30	Output: PWM for UVW to control Compressor(0~320VAC)	CN16	Output: 220V AC to control crankcase heater
CN17	Input: Temperature acquisition(0-5VDC)	CN60	Output: 0~220V AC to control 4-way valve
CN414	Output: 0~320VDC to control DC FAN	CN12/CN13	Output: Connection of the high voltage REACTOR)

Fig. 8 – Wiring Diagram Sizes 18K – 24K (Heat Pump Units)

WIRING DIAGRAMS (CONT)




Fig. 9 – Wiring Diagram Sizes 18K – 24K (Cooling Only Units)

GUIDE SPECIFICATIONS

HORIZONTAL DISCHARGE OUTDOOR UNITS

Size Range: 3/4 to 2 Ton Nominal Cooling and Heating Capacity
Model Number: DLCERA

PART 1 – GENERAL

1.01 System Description

- A. Outdoor air-cooled split system compressor sections suitable for on-the-ground, rooftop, wall hung or balcony mounting. Units consist of a rotary compressor, an air-cooled coil, propeller-type draw-through outdoor fan, reversing valve (HP), accumulator (HP units), metering device(s), and a control box. Units discharge air horizontally as shown on the contract drawings. Units function as the outdoor component of an air-to-air cooling only, or heat pump system.
- B. Units are to be used in a refrigeration circuit matched to ductless heat pump fan coil units.

1.02 Agency Listings

- A. Unit construction complies with ANSI/ASHRAE 15, latest revision, and with the NEC.
- B. Units are evaluated in accordance with UL standard 1995.
- C. Units are listed in the CEC directory.
- D. Unit cabinet is capable of withstanding 500-hour salt spray test per Federal Test Standard No. 141 (method 6061).
- E. Air-cooled condenser coils are leak tested at 550 psig.

1.03 Delivery, Storage, And Handling

Units are shipped in one piece and are stored and handled per unit manufacturer's recommendations.

1.04 Warranty (For Inclusion By Specifying Engineer)

PART 2 – PRODUCTS

2.01 Equipment

A. General:

Factory assembled, single piece, air-cooled outdoor unit. Contained within the unit enclosure is all the factory wiring, piping, controls, and the compressor.

B. Unit Cabinet:

1. Unit cabinet is constructed of galvanized steel, bonderized and coated with a baked-enamel finish on the inside and outside (PANTONE 7527U).
2. Unit access panels is removable with minimal screws and provides full access to the compressor, fan, and control components.
3. The outdoor compartment is isolated and has an acoustic lining to assure quiet operation.

C. Fans:

1. Outdoor fans are the direct drive propeller type, and discharges air horizontally. Fans draw air through the outdoor coil.
2. Outdoor fan motors are totally enclosed, single phase motors with class E insulation and permanently lubricated ball bearings. Motor shall be protected by internal thermal overload protection.
3. The shaft has inherent corrosion resistance.
4. Fan blades are non-metallic and statically and dynamically balanced.
5. Outdoor fan openings are equipped with a PVC metal/mesh coated protection grille over the fan.

D. Compressor:

1. Compressor is the fully hermetic rotary type.
2. Compressor is equipped with an oil system, operating oil charge, and a motor.
3. Motor is NEMA rated class E, suitable for operation in a refrigerant atmosphere.
4. Compressor assembly is installed on rubber vibration isolators.

E. Outdoor Coil:

The coil is constructed of aluminum golden hydrophilic pre-coated fins mechanically bonded to seamless copper tubes, which are cleaned, dehydrated, and sealed.

F. Refrigeration Components:

Refrigerant circuit components include a brass external liquid line service valve with service gage port connections, a suction line service valve with a service gage connection port, service gage port connections on compressor suction and discharge lines with Schrader type fittings with brass caps, accumulator, reversing valve.

G. Controls and Safeties:

Operating controls and safeties are factory selected, assembled, and tested. The minimum control functions include the following:

1. Controls:
 - a. A time delay control sequence is provided standard through the fan coil board
 - b. Automatic outdoor fan motor protection.
2. Safeties:
 - a. System diagnostics
 - b. Compressor motor current and temperature overload protection
 - c. Outdoor fan failure protection.

H. Electrical Requirements:

1. Unit operates on single-phase, 60 Hz power at 115V for unit size 12 and 208/230V for unit sizes 09, 12, 18, and 24 as specified.
2. Unit electrical power has a single point connection.
3. Unit Control voltage to the indoor fan coil is 0-15V DC.
4. All power and control wiring must be installed per NEC and all local electrical codes.
5. The unit has high and low voltage terminal block connections.