

HE Series

The High Efficiency HEH/V Series offers high efficient two-stage operation in a simple cabinet design. The High Efficiency Series also offers options that allow for application flexibility. Available options include hot water generator, enhanced iGate® controls, coated air coils, extended range insulation, UltraQuiet package, vFlow® internal variable water flow, and internal secondary circulator.

ADVANTAGE OF THE HIGH EFFICIENCY HEH/V SERIES

- Advanced Controls - iGate® communicating control provides advanced unit functionality and comprehensive configuration, monitoring and diagnostic capabilities through digital communication links with the variable-speed fan motor, variable-speed source pump (or modulating valve) and communicating thermostat or configuration/diagnostic tool
- Optional Internal Variable Water Flow - Industry-first, Built-in vFlow® replaces a traditionally inefficient, external component of the geothermal system (water circulation) with an ultra-high-efficient, variable speed, internal water flow system consisting of an internal variable speed circulator or an internal modulating motorized water valve
- Sound absorbing glass fiber insulation
- Unique double isolation compressor mounting for quiet operation
- Insulated divider and separate compressor/air handler compartments
- Field convertible discharge air arrangement for horizontal units
- Variable speed ECM fan motor
- Internally trapped condensate drain line (vertical units only)
- Eight safeties standard
- Extended range (20 to 120°F, -6.7 to 48.9°C) capable
- Tin-plated micro-channel EVAP coil
- SS drain pan

Vertical Upflow Model		A Width	B Depth	C Height
024 - 030	in. cm	22.4 56.9	22.4 56.9	40.5 102.9
036 - 042	in. cm	22.4 56.9	25.4 64.5	46.5 118.1
048 - 060	in. cm	25.4 64.5	29.1 73.9	50.5 128.3

Horizontal Model		A Width	B Length	C Height
024 - 030	in. cm	22.4 56.9	48.3 122.7	18.3 46.5
036 - 042	in. cm	22.4 56.9	53.1 134.9	21.3 54.1
048 - 060	in. cm	25.4 64.5	68.0 172.7	21.3 54.1

Comfort-Aire®

GEOHERMAL RESIDENTIAL PACKAGE UNITS

2 to 5 Tons
60Hz - HFC 410A



Warranty—10 years on compressor, 10 years on parts
(Some limitations apply; see printed warranty for details.)

www.marsdelivers.com

PHYSICAL DATA

Model	024	030	036	042	048	060
Compressor (1 Each)	Scroll					
Factory Charge HFC-410A (oz)	51	48	54	70	80	84
ECM Fan Motor & Blower						
Fan Motor (hp)	1/2	1/2	1/2	3/4	3/4	1
Blower Wheel Size (dia x w) - (in)	9X7	9X7	9X8	9X8	10X10	11X10
Water Connection Size						
FPT(in)	3/4"	3/4"	3/4"	3/4"	1"	1"
Coax Volume (gallons)	0.323	0.323	0.738	0.89	0.738	0.939
HWG Connection Size						
FPT(in)	1/2"					
Vertical Upflow						
Air Coil Dimensions (h x w) - (in)	20 X 17.25	20 X 17.25	24 X 21.75	24 X 21.75	28.75 X 24	28.75 X 24
Standard Filter - 1" [25.4mm] Throwaway, qty (in)	20x20	20x20	24x24	24x24	28x28	28x28
Weight - Operating, (lbs)	224	224	249	260	315	330
Weight - Packaged, (lbs)	229	229	255	266	322	337
Horizontal						
Air Coil Dimensions (h x w) - (in)	16 X 22	16 X 22	20 X 25	20 X 25	20 X 35	20 X 35
Standard Filter - 1" [25.4mm] Throwaway, qty (in)	18x25	18x25	20x28 or 2-20x14	20x28 or 2-20x14	1-20x24, 1-20x14	1-20x24, 1-20x14
Weight - Operating, (lbs)	208	208	233	244	299	314
Weight - Packaged, (lbs)	213	213	239	250	306	321

Notes: All units have TXV expansion device and 1/2" & 3/4" electrical knockouts.

TESTED TO ASHRAE/AHRI/ISO 13256-1 ENGLISH UNITS

Model	Water Loop Heat Pump				Ground Water Heat Pump				Ground Loop Heat Pump			
	Cooling 86°F		Heating 68°F		Cooling 59°F		Heating 50°F		Full Cool 77°F Part Cool 68°F		Full Heat 32°F Part Heat 41°F	
	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP
HE*024 Part	18,100	16.1	20,600	5.2	20,300	27.2	16,700	4.4	19,400	22.2	14,700	4.0
HE*024 Full	23,700	14.3	28,000	4.6	26,500	21.7	23,000	4.1	24,600	16.0	17,800	3.6
HE*030 Part	21,900	15.2	26,300	5.0	24,900	24.8	22,000	4.3	24,200	20.9	19,400	3.9
HE*030 Full	28,500	14.0	35,800	4.6	32,300	20.7	30,000	4.2	29,900	15.7	23,800	3.6
HE*036 Part	25,800	17.2	29,900	5.3	29,000	29.4	24,900	4.6	27,300	23.4	21,500	4.0
HE*036 Full	34,300	15.1	42,000	4.6	38,200	22.3	35,100	4.3	35,200	16.7	27,300	3.6
HE*042 Part	31,000	15.8	36,800	5.1	35,200	26.4	30,500	4.3	34,000	22.0	26,900	3.8
HE*042 Full	41,100	14.3	50,200	4.6	46,300	21.3	42,300	4.1	43,100	16.1	33,300	3.4
HE*048 Part	34,100	15.2	39,500	5.5	39,200	26.8	32,600	4.6	37,600	21.2	29,200	4.1
HE*048 Full	45,900	14.0	53,800	4.9	51,800	20.9	45,000	4.4	48,100	15.5	35,600	3.7
HE*060 Part	45,500	17.7	49,000	5.3	50,400	28.9	39,800	4.5	48,600	23.7	34,800	4.0
HE*060 Full	61,700	15.7	67,500	4.8	68,000	22.7	55,400	4.3	63,200	17.3	43,700	3.6

Cooling capacities based upon 80.6°F DB, 66.2°F WB entering air temperature. Heating capacities based upon 68°F DB, 59°F WB entering air temperature. All rating based upon operation at lower voltage of dual voltage rated models. * Includes vertical and horizontal configurations

Due to ongoing product improvements, specifications and dimensions are subject to change and correction without notice or incurring obligations. Determining the application and suitability for use of any product is the responsibility of the installer. Additionally, the installer is responsible for verifying dimensional data on the actual product prior to beginning any installation preparations.

Third party incentive and rebate programs have precise requirements as to product performance and certification. All products meet applicable regulations in effect on date of manufacture; however, certifications are not necessarily granted for the life of a product. Therefore, it is the responsibility of the applicant to determine whether a specific model qualifies for these incentive/rebate programs.

"This product complies with all California product labeling laws including, but not limited to, the Safe Drinking Water and Toxic Enforcement Act of 1986, more commonly known as Proposition 65."